

ABSTRACT OF THE DISCLOSURE

The invention relates to a regulating heat exchange and cooling method and system for monitoring and controlling the temperatures of walls subjected to high temperatures. The inventive system is used to cool the inner wall (7) of a thermal system comprising a double wall (9), said inner wall being subjected to temperatures equal to or greater than the physical capacity thereof. Said system also comprises a network of tubes (1) which is independent of the thermal system to be cooled. The aforementioned tubes (1) contain pressurised cooling water (4) which circulates therethrough. Moreover, said tubes are provided with nozzles (3) which are used to spray and project the water in the form of solid cones (5) against the inner wall (7), said nozzles being controlled by adjustable-flow valves (2). The above-mentioned network of tubes forms an integral part of the outer wall of the thermal system to be cooled and the system also comprises means of maintaining the water projection area defined by the inner and outer walls in a vacuum condition.

(12) DEMANDE INTERNATIONALE PUBLIÉE EN VERTU DU TRAITÉ DE COOPÉRATION
EN MATIÈRE DE BREVETS (PCT)

(19) Organisation Mondiale de la Propriété
Intellectuelle
Bureau international



(43) Date de la publication internationale
25 mars 2004 (25.03.2004)

PCT

(10) Numéro de publication internationale
WO 2004/025201 A3

(51) Classification internationale des brevets⁷ : F27D 9/00

(21) Numéro de la demande internationale :
PCT/FR2003/002734

(22) Date de dépôt international :
16 septembre 2003 (16.09.2003)

(25) Langue de dépôt : français

(26) Langue de publication : français

(30) Données relatives à la priorité :
02/11458 16 septembre 2002 (16.09.2002) FR

(71) Déposant (pour tous les États désignés sauf US) : BIO
3D APPLICATIONS [FR/FR]; 15, rue de Turin, F-75008
Paris (FR).

(72) Inventeur; et

(75) Inventeur/Déposant (pour US seulement) : GUY-
OMARC'H Raymond [FR/FR]; Rue de Liqueette, Le
Village, F-30260 Saint Theodoric (FR).


(74) Mandataires : ALLANO, Sylvain etc.; Pontet Allano &
Associés SELARL, 25, rue Jean Rostand, Parc-Club Orsay-
Université, F-91893 Orsay Cedex (FR).

(81) États désignés (national) : AE, AG, AL, AM, AT, AU, AZ,
BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ,
DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,

[Suite sur la page suivante]

(54) Title: REGULATING HEAT EXCHANGE AND COOLING METHOD AND SYSTEM FOR MONITORING AND CONTROLLING THE TEMPERATURES OF WALLS SUBJECTED TO HIGH TEMPERATURES

(54) Titre : SYSTÈME ET PROCÉDÉ DE REFROIDISSEMENT ET D'ÉCHANGE THERMIQUE RÉGULATEUR, POUR LE CONTRÔLE ET LA MAÎTRISE DES TEMPÉRATURES DE PAROIS SOUMISES À HAUTES TEMPÉRATURES



1. PRESSURE LESS THAN 1 BAR
2. HEAT SOURCES
3. THERMAL RADIATION CONVECTION
4. DIRECT FLAMES
5. SOLID FUEL AT VERY HIGH TEMPERATURES
6. THERMAL CONDUCTIVITY

(57) Abstract: The invention relates to a regulating heat exchange and cooling method and system for monitoring and controlling the temperatures of walls subjected to high temperatures. The inventive system is used to cool the inner wall (7) of a thermal system comprising a double wall (9), said inner wall being subjected to temperatures equal to or greater than the physical capacity thereof. Said system also comprises a network of tubes (1) which is independent of the thermal system to be cooled. The aforementioned tubes (1) contain pressurised cooling water (4) which circulates therethrough. Moreover, said tubes are provided with nozzles (3) which are used to spray and project the water in the form of solid cones (5) against the inner wall (7), said nozzles being controlled by adjustable-flow valves (2). The above-mentioned network of tubes forms an integral part of the outer wall of the thermal system to be cooled and the system also comprises means of maintaining the water projection area defined by the inner and outer walls in a vacuum condition.

(57) Abrégé : « Système et procédé de refroidissement et d'échange thermique régulateur, pour le contrôle et la maîtrise des températures de parois soumises à hautes températures » Système pour refroidir une paroi interne (7) d'un système thermique comportant une double paroi (9), ladite paroi interne étant soumise à des températures égales ou supérieures à sa

[Suite sur la page suivante]

WO 2004/025201 A3